


姿図



品 番	DDL-4813FB
光 源	LED 8.4W (5000K/3500K/2700K)
定格光束	570.0 lm
1/2照度角	62°
ビーム角	90°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.20 H B 1.20 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		54	46	41	53	46	41	52	46	41	51	45	41	39
0.8		64	57	51	64	56	51	62	55	51	60	55	50	48
1		73	65	60	72	65	59	70	63	59	68	62	58	56
1.25		80	73	68	79	72	67	77	71	66	75	70	66	63
1.5		86	79	74	85	78	73	82	77	72	79	75	71	68
2		94	88	83	92	87	83	89	85	81	86	83	79	76
2.5		99	94	90	97	92	89	94	90	87	91	87	85	81
3		102	98	94	100	96	93	97	94	91	94	91	89	85
4		106	103	100	104	101	98	100	98	95	97	95	93	88
5		109	106	103	107	104	101	102	100	98	99	97	95	91

